

VYM18-5

DIESEL GENERATOR SET / SILENT



18

kVA

STANDBY POWER

17

kVA

PRIME POWER

50

Hz

FREQUENCY

400/230

V

VOLTAGE

Yanmar 4TNV88-GGE

3 phase · 0.8 PF · 1500 rpm

CONFIGURATION COMPARISON

Configuration	Dimensions (L × W × H)	Dry weight	Fuel tank
Silent set	2000 × 900 × 1276 mm	759 kg	80 L

Performance, engine, alternator and controller data are common to both configurations.

GENERAL CHARACTERISTICS

VYM18-5 · 50 Hz · 3 Phase

RATED PERFORMANCE

Standby Power (kVA)	18
Standby Power (kW)	15
Prime Power (kVA)	17
Prime Power (kW)	13.6
Power Factor (Cos Phi)	0.8
Diesel Engine	4TNV88-GGE
Frequency (Hz)	50
Rated Speed (rpm)	1500
Phase	3
Standard Voltage (V)	400/230
Available Voltages (V)	380/220 · 415/240

POWER DEFINITIONS

STANDBY POWER (ESP)

Available for supplying emergency power during a utility interruption. The stated rating follows ISO 8528-1.

PRIME POWER (PRP)

Available for an unlimited number of annual operating hours in variable-load applications, in accordance with ISO 8528-1.

TERMS OF USE

Nominal power is stated at 25 °C inlet-air temperature, 100 kPa barometric pressure (100 m A.S.L.) and 30% relative humidity.

RATED OUTPUT CURRENT BY VOLTAGE

Rated voltage	Standby current (18 kVA)	Prime current (17 kVA)
380/220 V	27.3 A	25.8 A
400/230 V	26.0 A	24.5 A
415/240 V	25.0 A	23.7 A

ENGINE DATA

Yanmar 4TNV88-GGE

GENERAL ENGINE DATA

Engine brand	Yanmar
Engine model	4TNV88-GGE
Engine type	4-stroke diesel
Governor type	Mechanical
Injection type	Direct
Aspiration type	Natural aspirated
Cylinders and arrangement	4-L

FUEL CONSUMPTION

100% load ESP	/
100% load PRP	3.9 L/h
75% load PRP	/
50% load PRP	/

AIR SYSTEM

Intake air flow	24.7 L/s
Cooling air flow	/

GENERAL ENGINE DATA

Bore × stroke	88 × 90 mm
Displacement	2.2 L
Cooling system	Water-cooled
Lube oil consumption at full load	0.5%-1% of fuel consumption
Compression ratio	19.1:1
Air filter	Dry

EXHAUST SYSTEM

Maximum exhaust temperature	470 °C
Exhaust gas flow	70.7 L/s
Maximum allowed back pressure	15.3 kPa

STARTING SYSTEM

Starting power	1.4 kW
Recommended battery	60 Ah
Number of batteries	1
Auxiliary voltage	12 VDC

OIL AND COOLING CAPACITIES

Engine oil capacity	7.4 L
Total coolant capacity	2.7 (Engine) L

ALTERNATOR DATA

3-phase · Brushless · Electronic AVR

GENERAL ALTERNATOR DATA

Number of phases	3
Power factor (Cos Phi)	0.8
Poles	4
Winding connections (standard)	Star-series
Insulation	H class
Enclosure (according to IEC 34-5)	IP23
Excitation system	Self-excited, brushless
Voltage regulator	AVR (Electronic)
Number of bearings	Single bearing
Coupling system	Flexible disc
Coating type	Standard (vacuum impregnation)

CONTROL MODULE

ComAp IntelliNano AMF 5



AUTOMATIC MAINS FAILURE

AMF CONTROL

Provides automatic mains failure control plus manual or remote start/stop, with generator and mains measurement, protection, event logging and timer functions.

CORE FUNCTIONS

- | | | | |
|----|---|----|---|
| 01 | Automatic Mains Failure plus manual or remote start/stop | 05 | Detailed event history with up to 100 records for fault analysis |
| 02 | Configuration, commissioning and monitoring through IntelliConfig | 06 | USB-C for configuration/firmware update; CAN supports J1939 communication |
| 03 | 3-phase generator and mains voltage measurement, plus 3-phase generator current measurement | 07 | User setpoints, protections and dedicated emergency-stop functionality |
| 04 | 6 binary outputs, 4 + 1 binary inputs and 3 analog inputs for flexible I/O integration | 08 | One slot for optional Ethernet, 4G-GPS or dual-port RS232/RS485 module |

CONNECTIVITY

InteliNano AMF 5 · Communication options

- USB-C
- CAN / J1939
- INTERNET
- MODBUS RTU

COMMUNICATION AND MONITORING FEATURES

- 01

USB-C supports controller configuration and firmware updates, including power-over-USB-C
- 02

CAN interface supports J1939 communication with compatible engine ECUs
- 03

One plug-in slot: choose Ethernet, 4G-GPS or dual-port RS232/RS485 (HW 2.0+)
- 04

Remote monitoring support via AirGate 2.0, WebSupervisor and InteliScada
- 05

Internet access is available through the optional Ethernet or 4G-GPS module
- 06

Modbus RTU is available through the optional dual-port RS232/RS485 module
- 07

4G-GPS supports geo-fencing; User Access Management improves access control

PLUG-IN MODULES

CM3-ETHERNET · CM2-4G-GPS · CM-RS232-485

Only one module can be installed. Plug-in support requires controller HW 2.0 or higher.