

VFP33-5

DIESEL GENERATOR SET / SILENT



kVA
STANDBY POWER

30
kVA
PRIME POWER

50
Hz
FREQUENCY

400/230
V
VOLTAGE

FPT R24MSNS01.31A01

3 phase · 0.8 PF · 1500 rpm

CONFIGURATION COMPARISON

Configuration	Dimensions (L × W × H)	Dry weight	Fuel tank
Silent set	2150 × 950 × 1250 mm	960 kg	80 L

Performance, engine, alternator and controller data are common to both configurations.

GENERAL CHARACTERISTICS

VFP33-5 · 50 Hz · 3 Phase

RATED PERFORMANCE

Standby Power (kVA)	
Standby Power (kW)	26
Prime Power (kVA)	30
Prime Power (kW)	24
Power Factor (Cos Phi)	0.8
Diesel Engine	R24MSNS01.3 1A01
Frequency (Hz)	50
Rated Speed (rpm)	1500
Phase	3
Standard Voltage (V)	400/230
Available Voltages (V)	380/220 · 415/240

POWER DEFINITIONS

STANDBY POWER (ESP)

Available for supplying emergency power during a utility interruption. The stated rating follows ISO 8528-1.

PRIME POWER (PRP)

Available for an unlimited number of annual operating hours in variable-load applications, in accordance with ISO 8528-1.

TERMS OF USE

Nominal power is stated at 25 °C inlet-air temperature, 100 kPa barometric pressure (100 m A.S.L.) and 30% relative humidity.

RATED OUTPUT CURRENT BY VOLTAGE

Rated voltage	Standby current (kVA)	Prime current (30 kVA)
380/220 V	/	45.6 A
400/230 V	/	43.3 A
415/240 V	/	41.7 A

ENGINE DATA

FPT R24MSNS01.31A01

GENERAL ENGINE DATA

Engine brand	FPT
Engine model	R24MSNS01.31A01
Engine type	4-stroke diesel
Governor type	Mech
Injection type	Direct
Aspiration type	Turbocharged
Cylinders and arrangement	4-L

FUEL CONSUMPTION

100% load ESP	9.4 L/h
100% load PRP	8.6 L/h
75% load PRP	6.5 L/h
50% load PRP	4.4 L/h

AIR SYSTEM

Intake air flow	61.9 L/s
Cooling air flow	/

GENERAL ENGINE DATA

Bore × stroke	87 × 103 mm
Displacement	2.4 L
Cooling system	Water-cooled
Lube oil consumption at full load	< 0.1% of fuel consumption
Compression ratio	17.8:1
Air filter	Dry

EXHAUST SYSTEM

Maximum exhaust temperature	630 °C
Exhaust gas flow	0.078 kg/s
Maximum allowed back pressure	10 kPa

STARTING SYSTEM

Starting power	2.3 kW
Recommended battery	60 Ah
Number of batteries	1
Auxiliary voltage	12 VDC

OIL AND COOLING CAPACITIES

Engine oil capacity	10.5 L
Total coolant capacity	7.6 L

ALTERNATOR DATA


3-phase · Brushless · Electronic AVR

GENERAL ALTERNATOR DATA

Number of phases	3
Power factor (Cos Phi)	0.8
Poles	4
Winding connections (standard)	Star-series
Insulation	H class
Enclosure (according to IEC 34-5)	IP23
Excitation system	Self-excited, brushless
Voltage regulator	AVR (Electronic)
Number of bearings	Single bearing
Coupling system	Flexible disc
Coating type	Standard (vacuum impregnation)

CONTROL MODULE

ComAp IntelliNano AMF 5



AUTOMATIC MAINS FAILURE

AMF CONTROL

Provides automatic mains failure control plus manual or remote start/stop, with generator and mains measurement, protection, event logging and timer functions.

CORE FUNCTIONS

- | | | | |
|----|---|----|---|
| 01 | Automatic Mains Failure plus manual or remote start/stop | 05 | Detailed event history with up to 100 records for fault analysis |
| 02 | Configuration, commissioning and monitoring through IntelliConfig | 06 | USB-C for configuration/firmware update; CAN supports J1939 communication |
| 03 | 3-phase generator and mains voltage measurement, plus 3-phase generator current measurement | 07 | User setpoints, protections and dedicated emergency-stop functionality |
| 04 | 6 binary outputs, 4 + 1 binary inputs and 3 analog inputs for flexible I/O integration | 08 | One slot for optional Ethernet, 4G-GPS or dual-port RS232/RS485 module |

CONNECTIVITY

InteliNano AMF 5 · Communication options

- USB-C
- CAN / J1939
- INTERNET
- MODBUS RTU

COMMUNICATION AND MONITORING FEATURES

- 01

USB-C supports controller configuration and firmware updates, including power-over-USB-C
- 02

CAN interface supports J1939 communication with compatible engine ECUs
- 03

One plug-in slot: choose Ethernet, 4G-GPS or dual-port RS232/RS485 (HW 2.0+)
- 04

Remote monitoring support via AirGate 2.0, WebSupervisor and InteliScada
- 05

Internet access is available through the optional Ethernet or 4G-GPS module
- 06

Modbus RTU is available through the optional dual-port RS232/RS485 module
- 07

4G-GPS supports geo-fencing; User Access Management improves access control

PLUG-IN MODULES

CM3-ETHERNET · CM2-4G-GPS · CM-RS232-485

Only one module can be installed. Plug-in support requires controller HW 2.0 or higher.