

VW33-5

DIESEL GENERATOR SET / SILENT



33

kVA

STANDBY POWER

30

kVA

PRIME POWER

50

Hz

FREQUENCY

400/230

V

VOLTAGE

Weichai WP2.3D33E200

3 phase · 0.8 PF · 1500 rpm

CONFIGURATION COMPARISON

Configuration	Dimensions (L × W × H)	Dry weight	Fuel tank
Silent set	2150 × 950 × 1250 mm	830 kg	80 L

Performance, engine, alternator and controller data are common to both configurations.

GENERAL CHARACTERISTICS

VW33-5 · 50 Hz · 3 Phase

RATED PERFORMANCE

Standby Power (kVA)	33
Standby Power (kW)	26
Prime Power (kVA)	30
Prime Power (kW)	24
Power Factor (Cos Phi)	0.8
Diesel Engine	WP2.3D33E200
Frequency (Hz)	50
Rated Speed (rpm)	1500
Phase	3
Standard Voltage (V)	400/230
Available Voltages (V)	415/240 or 380/220

POWER DEFINITIONS

STANDBY POWER (ESP)

Available for supplying emergency power during a utility interruption. The stated rating follows ISO 8528-1.

PRIME POWER (PRP)

Available for an unlimited number of annual operating hours in variable-load applications, in accordance with ISO 8528-1.

TERMS OF USE

Nominal power is stated at 25 °C inlet-air temperature, 100 kPa barometric pressure (100 m A.S.L.) and 30% relative humidity.

RATED OUTPUT CURRENT BY VOLTAGE

Rated voltage	Standby current (33 kVA)	Prime current (30 kVA)
380/220 V	50.1 A	45.6 A
400/230 V	47.6 A	43.3 A
415/240 V	45.9 A	41.7 A

ENGINE DATA

Weichai WP2.3D33E200

GENERAL ENGINE DATA

Engine brand	Weichai
Engine model	WP2.3D33E200
Engine type	4-stroke diesel
Governor type	Electronic
Injection type	Direct
Aspiration type	Turbocharged
Cylinders and arrangement	4-L

FUEL CONSUMPTION

100% load ESP	8.4 L/h
100% load PRP	7.6 L/h
75% load PRP	5.7 L/h
50% load PRP	4 L/h

AIR SYSTEM

Intake air flow	30.7 L/s
Cooling air flow	/

GENERAL ENGINE DATA

Bore × stroke	89 × 92 mm
Displacement	2.3 L
Cooling system	Water-cooled
Lube oil consumption at full load	0.5%-1% of fuel consumption
Compression ratio	17.5:1
Air filter	Dry

EXHAUST SYSTEM

Maximum exhaust temperature	650 °C
Exhaust gas flow	32.1 L/s
Maximum allowed back pressure	8 kPa

STARTING SYSTEM

Starting power	3 kW
Recommended battery	60 Ah
Number of batteries	1
Auxiliary voltage	12 VDC

OIL AND COOLING CAPACITIES

Engine oil capacity	8 L
Total coolant capacity	5 (Engine only) L

ALTERNATOR DATA

3-phase · Brushless · Electronic AVR

GENERAL ALTERNATOR DATA

Number of phases	3
Power factor (Cos Phi)	0.8
Poles	4
Winding connections (standard)	Star-series
Insulation	H class
Enclosure (according to IEC 34-5)	IP23
Excitation system	Self-excited, brushless
Voltage regulator	AVR (Electronic)
Number of bearings	Single bearing
Coupling system	Flexible disc
Coating type	Standard (vacuum impregnation)

CONTROL MODULE

ComAp IntelliNano AMF 5



AUTOMATIC MAINS FAILURE

AMF CONTROL

Provides automatic mains failure control plus manual or remote start/stop, with generator and mains measurement, protection, event logging and timer functions.

CORE FUNCTIONS

01	Automatic Mains Failure plus manual or remote start/stop	05	Detailed event history with up to 100 records for fault analysis
02	Configuration, commissioning and monitoring through IntelliConfig	06	USB-C for configuration/firmware update; CAN supports J1939 communication
03	3-phase generator and mains voltage measurement, plus 3-phase generator current measurement	07	User setpoints, protections and dedicated emergency-stop functionality
04	6 binary outputs, 4 + 1 binary inputs and 3 analog inputs for flexible I/O integration	08	One slot for optional Ethernet, 4G-GPS or dual-port RS232/RS485 module

CONNECTIVITY

InteliNano AMF 5 · Communication options

USB-C

CAN / J1939

INTERNET

MODBUS RTU

COMMUNICATION AND MONITORING FEATURES

- 01

USB-C supports controller configuration and firmware updates, including power-over-USB-C
- 02

CAN interface supports J1939 communication with compatible engine ECUs
- 03

One plug-in slot: choose Ethernet, 4G-GPS or dual-port RS232/RS485 (HW 2.0+)
- 04

Remote monitoring support via AirGate 2.0, WebSupervisor and InteliScada
- 05

Internet access is available through the optional Ethernet or 4G-GPS module
- 06

Modbus RTU is available through the optional dual-port RS232/RS485 module
- 07

4G-GPS supports geo-fencing; User Access Management improves access control

PLUG-IN MODULES

CM3-ETHERNET · CM2-4G-GPS · CM-RS232-485

Only one module can be installed. Plug-in support requires controller HW 2.0 or higher.